

SIYARAM PUMP

Description

SIYARAM Pump is specially formulated to meet the engine oil requirements of agricultural pump sets. It is manufactured from premium quality base oil and carefully selected additives.

Application

This oil is recommended for agricultural pump sets working in different climatic conditions. It is also recommended for threshers, sugarcane harvesters / crushers etc.

Benefits

□ BETTER PERFORMANCE -Better resistance against wear of moving engine parts at all operating conditions due to
antiwear properties.
□ LONGER OIL LIFE - Outstanding thermo oxidative stability reduces consumption, filter blocking and valve sticking.
□ ENGINE LIFE- Protects engine components against rust due to rust inhibitors and corrosion due to built-in alkaline
reserves.
LESS MAINTANENCE - Premium detergent and dispersant additive technology lead to cooler and cleaner engine

□ **LESS MAINTANENCE** - Premium detergent and dispersant additive technology lead to cooler and cleaner engine for all the seasons.

PERFORMANCE LEVEL

🗆 API C) ر	
---------	-----	--

□ IS 13656 : 2002 EDL 1 □ US MIL-L-2104B

Technical Specifications

Characteristics	ASTM	SIYARAM PUMP 40
Appearance		Clear & Bright
Colour, Visual Observation		Red
Density @15°C, gm/ml	D1298	0.8880
K.V at 100° C, cSt	D445	14.4
Copper Corrosion @ 100°	D130	1a
C for 3 hrs		
Flash Point, (COC), °C	D92	222
Viscosity Index	D2270	96
Pour Point, °C	D97	-8
Foaming Tendency /	D892	Nil / Nil
Stability: Qty. of foam in ml		10 / Nil
a) Sequence I		Nil / Nil
b) Sequence II		
c) Sequence III		

Siyaram Petrotech Pvt. Ltd

Technical Services

51, Bhupen Bose Avenue, Kolkata - 700004

Phone - 033 25337211, Fax: 033 25555651 / 25559554

Email: info@siyarampetrotech.com



All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

Indoor Storage is always preferable.

□ Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
□ Barrels should be kept away from dusty or heated areas.
□ During handling any contact with dust must be avoided.
Health & Safety
This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS)

Advice

may be referred.

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Email: info@siyarampetrotech.com