

SIYARAM SPIROL BHT

Description

This is premium quality multi functional Tractor oil formulated from superior quality base oils together with specially selected performance additive components.

Application

This oil is recommended for farm tractors, agricultural machinery and construction equipment requiring common oil to meet lubrication requirements of transmission, hydraulic circuits, in-board wet brake and axles.

Benefits

☐ Superior oxidation stability
☐ Provides outstanding rust & corrosion protection
Excellent wet brake, anti-squak and low temperature properties

PERFORMANCE LEVEL LEVEL

	John Deere JD 20C
	Ford ESN-M2C-134D
П	Volvo WB 101

Technical Specifications

Characteristics	ASTM	SIYARAM SPIROL BHT 10w- 30
Appearance		Clear
Colour, Visual Observation		Bright
Density @15°C, gm/ml	D1298	0.8627
K.V at 100° C, cSt	D445	10.2
Viscosity Index	D2270	120
Flash Point, (COC), °C	D92	204
Pour Point, °C	D97	-30
Rust protection, 24hrs.		No rust after test

All the mentioned values are typical which may vary from batch to batch.

Siyaram Petrotech Pvt. Ltd Technical Services

51, Bhupen Bose Avenue, Kolkata - 700004

Phone - 033 25337211, Fax: 033 25555651 / 25559554

Email: <u>info@siyarampetrotech.com</u>



Storage and Handling

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

Email: info@siyarampetrotech.com

